


B3 temperature of at least 185°C, preferably at least 200°C and more preferably around 220°C.

REMARKS

• The claims have been amended to correct improper multiple dependent claims.

The application has been amended to add an abstract.

Respectfully submitted,


Joseph B. Lerch
Reg. No. 26,936
Attorney for Applicant(s)

DARBY & DARBY P.C.
805 Third Avenue, 27th Flr.
New York, NY 10022
212-527-7700

M:\3463\01445\SS4218.WPD

EXPRESS MAIL CERTIFICATE

DATE

1/4/02

LABEL NO.

2767721406US

I HEREBY CERTIFY THAT, ON THE DATE INDICATED ABOVE
THIS PAPER OR FEE WAS DEPOSITED WITH THE U.S. POSTAL SERVICE
& THAT IT WAS ADDRESSED FOR DELIVERY TO THE COMMISSIONER
OF PATENTS & TRADEMARKS, WASHINGTON, DC 20231 BY "EXPRESS
MAIL POST OFFICE TO ADDRESSEE" SERVICE.

NAME (PRINT)

SIGNATURE

PLEASE CHARGE ANY DEFICIENCY UP TO \$300.00 OR
CREDIT ANY EXCESS IN THE FEES DUE WITH THIS
DOCUMENT TO OUR DEPOSIT ACCOUNT NO. 04-0100

Customer No.:



07278

PATENT TRADEMARK OFFICE



Docket No.: 3463/OJ445

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Camille BORER ET AL.

Serial No: 09/910,435

Filed: July 20, 2001

For: DEVICE AND METHOD FOR TREATING PLASTIC MATERIAL

AMENDMENT MARK-UP SHEET FOR PRELIMINARY AMENDMENT
OF JANUARY 4, 2001

Commissioner of Patents and Trademarks
Washington DC 20231

In The Claims:

Please rewrite Claims 4-7 to read as follows:

4. (Amended) A device according to [one of the preceding] claims
1 or 2, characterised in that a partition wall (13) is provided below the feed

aperture (14), for deflecting the incoming plastic material by means of a funnel section (13'), so as to deflect the material to a preceding compartment (12'), thus at least partially covering the subsequent compartment (12'') by the funnel section (13').

5. (Amended) A device according to [one of the preceding] claims 1 or 2, characterised in that the first compartment (12') takes up more than half, preferably more than 2/3 of the area in top view of the treatment space (12) which is at least approximately rotation-symmetrical, and that this first compartment (12') is followed by a second compartment (12'') which is accordingly smaller.

6. (Amended) A device according to [one of the preceding] claims 1 or 2, characterised in that a monitoring arrangement such as an inspection glass (24) is associated with at least one compartment (12''), e.g. the last compartment.

7. (Amended) A device according to [one of the preceding] claims 1 or 2, characterised in that the floor region of the treatment space (12) is the perforated floor (16) of a fluidised bed.

Please rewrite Claims 16 and 17 to read as follows:

16. (Amended) A method according to one of [the preceding] claims 8, 9, 12 or 13, characterised in that precrystallisation and crystallisation are preferably carried out within a duration of 10 to 80 minutes, preferably 15 to 40 minutes, in particular within approx. 20 to 30 minutes.

17. (Amended) A method according to one of [the preceding] claims 8, 9, 12 or 13, characterised in that heating following crystallisation, including precondensation, takes place within a duration of 60 to 120 minutes, in particular approx. 90 minutes.